


BTS80



Rating: Not Rated Yet

[Ask a question about this product](#)

Manufacturer [Dorma](#)

Description

Center Hung Packages (A,B,G,H)

3/4" Offset Packages (D,E,F)

1-1/2" Offset Packages (C)

Pocket Door Packages (P)
Pocket Fire Door Packages (PF)

Independent Hung Packages (I)

Independent Hung Fire Door Packages (IF)

P applications can mortise the track in the door. PF applications surface apply track to door for U.L. fire door listing.

Track is surface applied to the door for U.L. fire door listing.

Spindles

Spindle No.	Dimension "X" (Door Clearance)	Offset Spindle No.	Dimension "Y"
74003	9/16"	80053	1/8"
74005	5/8"	80005	5/16"
74007	5/8"	80010	7/16"
(STD)74010	3/4"	80015	1"
74012	13/16"	80020	5/8"
74015	7/8"	80025	11/16"
74020	1-1/8"	80030	7/8"
74025	1-5/16"	80035	1"
74030	1-1/2"	80040	1-5/16"
74035	1-11/16"	-	1-1/2"
74040	1-7/8"	-	1-11/16"
74045	2-1/16"	-	1-7/8"
74050	2-5/16"	-	2-1/16"

Extended Spindle Insert

Offset Spindles
Spindles are available with a 3" offset for additional pressure to hold door in the closed position. Normally, this is only necessary for center- pivoted single acting applications. However, they can also be used with other applications to compensate for templating errors. Specify hand of offset spindle when ordering.

NOTE: Closer and arm must be installed per template for door clearances shown to be valid.
Closers with extended spindle inserts are used with thresholds, carpeted floors, linoleum parts or in cases where more clearance between door and floor is required. All spindles are zinc plated.